
ANSYS Magnetostatic and Structural Analyses of the sPHENIX Magnet at Full Current


John Cozzolino August 17, 2016

- Final comparison of Maxwell axial and radial coil forces
 (7/28/16) to Wuzheng Meng's 2D results from 6/17/15
 - Forces track acceptably (see following chart).
 - The 2D Maxwell axisymmetric simulation has functioned properly and generates valid results.




Labels on 24 Solenoid Coils


(Not to Scale) W. Meng, 6/17/15



- 3D magnetostatic FE analysis of the coil in the iron
 - Geometry is taken from the simplified Creo solid model.
 - The coil center is shifted 3cm north relative to the iron.
 - » The iron weight is approximately 1,320,000 lb.
 - » The fringe B field outside the iron is observed at 4600 A.
 - » The simplified 3D FE model is used to compare end forces on the iron to Wuzheng's calculations from 6/17/2015.




 Axial Forces on sPHENIX Iron End Caps at 4600 A with 3 & 4 cm Coil Offsets North




		S Iron (lbf)	N Iron (lbf)	Delta (lbf)
3cm Offset	Wuzheng	154267	181716	27449
3cm Offset	Maxwell	162000	193000	31000
4cm Offset	Maxwell	137000	199000	62000

- 3D magnetostatic and static structural FE analysis of the iron at 4600 A
 - Geometry is taken from the latest Creo solid model.
 - One side wall includes actual physical features and realistic contact conditions.
 - » Therefore, deflections should better represent actual behavior.



One side wall is modeled in detail.

- Frictionless contact is applied where appropriate.
- Bolts are in place but are not preloaded in the model.
- Max inward deflection is .011 inch (blue).
 - Note: This model lacks some of the latest features such as heavy angle braces and additional fasteners.
 - The effect of such iron deflections on the cryostat via its support struts has not yet been studied.



- Structural FE analysis of the cryostat support system is the logical next step.
 - The yoke assembly should include all newly added relevant features including steel gussets, additional bracing, and doublers.
 - Effects of the 30,000 lbf axial load imbalance should be considered as well.
 - Consider verifying the axial location of the solenoid relative to the iron.